

REVO Residential Energy Storage Inverters

# Split-Phase hybrid inverter

Battery low voltage



## Product Features:

### Safe & Reliable

- Passed UL 1741:2021, IEEE 1547.1, UL1699B, South Africa NRS097-2-1:2017 test certification.

### Friendly & Flexible

- Max. 3 pcs in parallel.
- Support multi-machine parallel mode sharing a battery pack.
- Single-machine load capacity 100A.

### Economical & Efficient

- Support parallel SOC equalization control and parallel current sharing control.
- Using split-phase topology and eliminating the transformers, to make the system efficiency higher.
- Support the diesel generator and the grid access at the same time.



**PV string input**

Model	R5KLNA	R6KLNA	R8KLNA	R10KLNA
Max. power (kW)	7.5	9	12	13
Max. DC voltage (V)	500			
MPPT voltage range (V)	120~500			
Max.input current of single MPPT (A)	14			
No. of MPPT trackers	4			
No. of strings per MPPT trackers	1			

**AC output**

Rated output power (kVA)	5	6	8	10
Max. apparent power (kVA)	5.5	6.6	8.8	11
Rated output current (A)	20.8	25	33.3	41.7
AC output voltage (V)	120/240(split phase),240 (single phase)			
Frequency (Hz)	50/60			
PF	0.8lagging-0.8leading			
THDi	< 2%			
AC output topology	Split phase,2/3 phase,single phase			

**Battery**

Battery voltage range (V)	40~58			
Max. charging voltage (V)	58			
Max. charge/discharge current (A)	120/120	135/135	190/190	190/210
Battery type	lithium /Lead-acid			
Communication interface	CAN			

**EPS output**

Rated power (kVA)	5	6	8	10
Rated output voltage (V)	120/240 (split phase),240 (single phase)			
Rated output current (A)	20.8	25	33.3	41.7
Rated frequency (Hz)	50/60			
Automatic switchover time (ms)	< 10			
THDu	< 2%			
Overload capacity	110%/60s, 120%/30s, 150%/10s			

**General data**

Max. efficiency	99.9%			
CEC efficiency	96.5%			
Ingress protection	IP65/Type 3R			
Operation temperature (°C)	-25 ~ 60 (>45 Derating)			
Noise emission(dB)	<38			
Cooling	Forced air			
Relative humidity	0 ~95% (non-condensing)			
Operating altitude	2,000m(>2,000 Derating)			
Dimensions W *D *H (mm)	460*225*760			
Net weight (kg)	41			
Topology	Non-isolated			
Self-consumption at night (W)	<25			

**Display and communication**

Display	LCD/touch screen			
Interface:RS485/Wifi/4G/ CAN/Bluetooth	Yes			
Safety standard	UL1741, CSA C22.2 No. 107.1:16,UL1998			
EMC	FCC Part 15, Class B			
On-grid	IEEE1547, CPUC Rule21, SRD V2.0, UL1741 SA, UL1741 SB			
DC ARC-Fault	UL1699B			